

SX1838-E

KIT SX STAPLER-CT/ST 38MM MAX

Diameter: 0.9 - 1.3mm
Crown: 5.6 - 5.6mm
Length: 12 - 38mm



Features

- 

Mg
- Magnesium Housing
- 

Rubber Comfort Grip
- Rubber Comfort Grip
- 

No-Mar-Tip
- No-Mar-Tip
- 

DIAL-A
- Dial-A-Depth
- 

Anti Slip Bumpers
- Anti Slip Bumpers
- 

Oil Free Engine
- Oil Free Engine
- 

Rear Exhaust
- Rear Exhaust
- 

Compact Nose
- Compact Nose
- 

Bottom Loading
- Bottom Loading
- 

Carry Case
- Carry Case
- 

Tool Lock-Out
- Tool Lock-Out
- 

CT
ST
- Selectable Trigger
- 

Locking Trigger
- Locking Trigger

SPECIFICATION						
EE =& get_instance(); ?>			Operating pressure		4.80 - 8.30 BAR	
Power type		Pneumatic				
Weight		1.36 kg		70.00 - 120.00 PSI		
Width		70 mm		Air Consumption Ltr.per shot @ 5.6 bar		
Length		235 mm		1.33		
Height		240 mm		Air fitting thread type		
Magazine capacity (max)		100		1/4 BSP		
Series Fasteners:			Noise	LPA 1sd	81.34	
				LWA 1sd	87.50	
				LPA 1s, 1m	75.50	
			Vibration / Uncertainty		3.06 / 1.53 m/s2	
Diameter (mm)		0.9 (min)	1.3 (max)			
Crown (mm)		5.6 (min)	5.6 (max)			
Length (mm)		12 (min)	38 (max)			
Collation type		EE->lang->language[""]; ?>				